U.S. Application No.: 10/533,240

AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions and listings of claims in the

application:

LISTING OF CLAIMS:

1-11. (canceled).

12. (currently amended): The hinge-lid pack according to Claim 1024, characterized

in that all four upright longitudinal edges (29, 30) are uniformly configured as a projection (35).

13. (currently amended): The hinge-lid pack according to Claim 1024, characterized

in that upper and lower transverse edges (31...34) for delimiting an end wall (18) and a base wall

(15) are configured as projections (35).

14. (currently amended): The hinge-lid pack according to Claim 10 or 1124 or 25,

characterized in that the collar (12) has upright collar edges (43, 44) which correspond in shape

to the longitudinal edges (29, 30).

15. (currently amended): The hinge-lid pack according to Claim 10 or 1124 or 25,

characterized in that box side tabs (23, 24) for the formation of box side walls (21) and lid side

tabs (25, 26) for the formation of lid side walls (22) overlap one another only in a region between

the assigned intermediate edges (36, 37).

2

Attorney Docket No.: Q87659

AMENDMENT UNDER 37 C.F.R. § 1.114(c) U.S. Application No.: 10/533,240

16. (currently amended): The hinge-lid pack according to Claim 1024, characterized in that for the configuration of the transverse edges (31, 32, 33, 34) as a projection (35), corner

tabs, namely base corner tabs (27) and/or end corner tabs (28) are configured with a width small enough such that the corner tabs (27, 28) can be positioned exclusively between the transverse

edges (31...34) configured as a projection (35).

17. (currently amended): The hinge-lid pack according to Claim 1024, characterized

in that each projection (35) has a radius of 1.5 mm to 4 mm.

18. (currently amended): The hinge-lid pack according to Claim 1024, characterized

by a blank which in its non-folded state is provided with embossments (46) or reinforcing seams

(47) formed by deformation and having an approximately semicircular-shaped cross-section in a

region of the longitudinal edges (29, 30) and transverse edges (31, 32, 33, 34), with the

projections (35) being formed by the folding of folding tabs or walls causing deformation of the

embossments (46) or reinforcing seams (47) such that, given a pre-determined dimension of the

embossments (46) or reinforcing seams (47), the projection (35) has a smaller radius than the

embossments (46) or reinforcing seams (47).

19. (currently amended): The hinge-lid pack according to Claim 4425, characterized

in that all four upright longitudinal edges (29, 30) are uniformly configured as a recess (40).

3

U.S. Application No.: 10/533,240

(currently amended): The hinge-lid pack according to Claim 4425, characterized
in that upper and lower transverse edges (31...34) for delimiting an end wall (18) and a base wall

(15) are configured as recesses (40).

21. (currently amended): The hinge-lid pack according to Claim 1125, characterized

in that for the configuration of the transverse edges (31, 32, 33, 34) as a recess (40), corner tabs,

namely base corner tabs (27) and/or end corner tabs (28) are configured with a width small

enough such that the corner tabs (27, 28) can be positioned exclusively between the transverse

edges (31...34) configured as a recess (40).

22. (currently amended): The hinge-lid pack according to Claim 1125, characterized

in that each recess (40) has a radius of 1.5 mm to 4 mm.

23. (currently amended): The hinge-lid pack according to Claim 1125, characterized

by a blank which in its non-folded state is provided with embossments (46) or reinforcing seams

(47) formed by deformation and having an approximately semicircular-shaped cross-section in a

region of the longitudinal edges (29, 30) and transverse edges (31, 32, 33, 34), with the recesses

(40) being formed by the folding of folding tabs or walls causing deformation of the

embossments (46) or reinforcing seams (47) such that, given a pre-determined dimension of the

embossments (46) or reinforcing seams (47), the recess (40) has a greater radius than the

embossments (46) or reinforcing seams (47).

4

U.S. Application No.: 10/533,240

24. (new): A hinge-lid pack, made of thin cardboard or similar packaging material for accommodating a cigarette group (48), and comprising a box part (10), lid (11) and collar (12), in each case with four upright pack edges, namely longitudinal edges (29, 30) and transverse edges (31, 32, 33, 34) running crosswise thereto, **characterized by** the following features:

- a) pack walls (14, 19; 16, 17; 21, 22), connected to each other in the region of the longitudinal edges (29, 30) and transverse edges (31, 32, 33, 34), are arranged at a right angle to each other.
- the longitudinal edges (29, 30) and/or transverse edges (31, 32, 33, 34) are configured, by deformation or embossing of the packaging material, as respective outwardly directed round projections (35),
- each projection (35) has a cross-section approximately in the shape of a threequarter circle.
- d) each projection (35) extends beyond the outer pack surface planes formed by the pack walls (14, 19; 16, 17; 21, 22), and
- e) each projection (35) is attached to adjacent pack walls and folding tabs by a respective intermediate edge (36, 37).
- 25. (new): A hinge-lid pack, made of thin cardboard or similar packaging material for accommodating a cigarette group (48), and comprising a box part (10), lid (11) and collar (12), in each case with four upright pack edges, namely longitudinal edges (29, 30) and

U.S. Application No.: 10/533,240

transverse edges (31, 32, 33, 34) running crosswise thereto, **characterized by** the following features:

- a) pack walls (14, 19; 16, 17; 21, 22), connected to each other in the region of the longitudinal edges (29, 30) and transverse edges (31, 32, 33, 34), are arranged at a right angle to each other.
- b) the longitudinal edges (29, 30) and/or transverse edges (31, 32, 33, 34) are configured, by deformation or embossing of the packaging material, as respective inwardly directed recesses (40) having a round cross-section,
 - c) each recess (40) has a cross-section approximately in the shape of a quarter circle,
- d) each recess (40) extends inwardly beyond the inner pack surface planes formed by the pack walls (14, 19; 16, 17; 21, 22), and
- e) each recess (40) is attached to the adjacent pack walls and folding tabs by a respective intermediate edge (36, 37).